



**Kaga Electronics(USA) Inc.**

## **ADAPTER-18W**

Wallmount/ U.K.

**Green Mode**

Meet CEC Regulations & RoHS Compliance



### **FEATURE**

Wallmount Type	U.K
Input range	90-264V/47~63Hz
Output	4.5V~24V/0.6A~3.5A(20W max.)
Efficiency	77% typical
Protection	Short Circuit, Over Voltage and Over Current Protection
Load regulation	±5%
Leakage current	Less than 0.25mA
M.T.B.F.	50,000 hours min. at 25°C, full load
Cable type	UL2468/18AWG or 20AWG
Dimension	72X50X59
Weight(reference)	165g

### **APPLICATION**

Broadband&Network Equipment , Wireless products, Portable Equipment

### **SAFETY & EMI**

Safety	CB/CE
EMI	CE Class B , conduction & Radiation MEET

### **ENVIRONMENTAL**

Operating temperature	0~+40°C
Storage Temperature	-20~+60°C
Relative Humidity	(operating)20~80%RH/(storage)10~90%RH

## MODEL

NO	MODEL NAME	Voltage(V)	Current(A)	Power(W)
1	STD-04535B	4.5	3.5	15.75
2	STD-05025B	5	2.5	12.5
3	STD-05030B	5	3	15
4	STD-05035B	5	3.5	17.5
5	STD-06025B	6	2.5	15
6	STD-06030B	6	3	18
7	STD-07025B	7	2.5	17.5
8	STD-07525B	7.5	2.5	18.75
9	STD-09015B	9	1.5	13.5
10	STD-09022B	9	2.2	19.8
11	STD-10019B	10	1.9	19
12	STD-12012B	12	1.2	14.4
13	STD-12016B	12	1.6	19.2
14	STD-13510B	13.5	1	13.5
15	STD-13514B	13.5	1.4	18.9
16	STD-15010B	15	1	15
17	STD-15013B	15	1.3	19.5
18	STD-16010B	16	1	16
19	STD-16012B	16	1.2	19.2
20	STD-18008B	18	0.8	14.4
21	STD-18011B	18	1.1	19.8
22	STD-20007B	20	0.7	14
23	STD-20010B	20	1	20
24	STD-24006B	24	0.6	14.4
25	STD-24008B	24	0.8	19.2

## MECHANICAL DRAWING

