



ADAPTER - 5W/10W



FEATURE

	5W	10W
Plug Tpye: U.S.A., U.K., Europe	U.S.A	∨
Input :100~240V/50~60 HZ	∨	∨
Input Range Voltage:90~264Vac,47~63HZ	∨	∨
Output power	5 watt max.	10 watt max
Efficiency	70%typical	70%typical
Short Circuit Protection	∨	∨
Over Voltage Protection	∨	∨
Over Current Protection	∨	∨
Leakage current: less than 0.25mA	∨	∨
Load Regulation ±5%	∨	∨
M.T.B.F.:50,000 hours min.	∨	∨
Cable type	UL2468/20AWG	UL2468/18AWG
Dimension:(L)x(W)x(H)mm	64x48x23	71x51x28
Weight	87g	115g

APPLICATION

PDA, MP2, DSC, CD-ROM, USB HUB, Wireless & Communication, Battery Charger

SAFTY & EMI

SAFETY	UL/cUL/GS/CB/PSE/BSMI	UL,cUL,BSMI	∨
EMI	CE ClassB, Conduction&Raditaton		∨

ENVIRONMENTAL

Operating Temperature:	0~ +40°C	∨	∨
Storage Temperature :	-20~ +60°C	∨	∨
Relative Humidly:operating	20~80%RH	∨	45~85%RH
Storage:	10~90%RH	∨	45~86%RH

RULE OF THE MODEL NAME

NO	MODEL NAME	Voltage(V)	Current(A)	Power(W)	INLET
1	STD-0315	3	1.5	4.5	U.S.A
2	STD-4201	4.2	1.1	4.62	U.S.A
3	STD-0501	5	1	5	U.S.A
4	STD-4215	4.2	1.5	6.3	U.S.A
5	EH-51	10.5	0.6	6.3	U.S.A
6	STD-0502	5	2	10	U.S.A
7	STD-0502	5	2	10	Japan
8	STD-0502	5	2	10	European
9	STD-0502	5	2	10	UK
10	STD-0912	9	1.2	10.8	U.S.A,Japan
11	STD-1201	12	1	12	U.S.A,Japan.CE
12	STD-1806	18	0.6	10.8	U.S.A
13	EH-52	8.4	1.3	10.92	U.S.A